



TIXXONLUBE XS SHC 460-2

Tixxonlube XS SHC 460-2 is a specialized synthetic high-temperature grease for paper machines. The product is used at temperatures from -40°C to +200°C, short-term withstands temperature increase up to 220°C.

Due to the sulfonate-calcium thickener in its composition the grease is able to provide protection not only in dry parts of paper machine, but also in wet sections. The lubricant is used in bearings of conveyor shafts, corrugators, hot air fans, as well as in gear wheels of rotary kiln drives.

Tixxonlube XS SHC 460-2 is resistant to oxidation, protects against corrosion even in acidic and alkaline environments, withstands high mechanical loads under significant watering.

TYPICAL PHYSICAL AND CHEMICAL PARAMETERS

PARAMETER	STANDARD	VALUE
Grease classification	DIN 51 502	KPHC2S-40
Colour, appearance	Visual	Brown
Thickener type	-	Calcium sulfonate complex
Type of base oil and additives	-	Synthetic (PAO)
Kinematic viscosity of the base oil at 40°C, mm ² /s	DIN 51 562	460
Kinematic viscosity of the base oil at 100°C, mm ² /s	DIN 51 562	48,2
NLGI class	DIN 51 818	2
Mixed grease penetration (60 double strokes), mm/10	DIN ISO 2137	265-295
Drop point, °C	DIN ISO 2176	290
Corrosion on copper plate	ASTM D4048	1a
Welding load at 25°C, N	DIN 51 350	3920
Wear scar diameter, mm	DIN 51 350	0,5
Temperature range, °C	-	-40...+200

* Values of the given parameters are typical for currently manufactured products, in the future they can be changed in accordance with the requirements of the manufacturer's specifications.



TIXXON

Technical specifications of Tixxonlube XS SHC 460-2
Product Code: XS SHC 460-2 Revision 20231127 v.2.0



TIXXONLUBE XS SHC 460-2

SAFETY PRECAUTIONS FOR USE

The product is inflame-resistant and belongs to the third hazard class. Before use, read the technical description, safety data sheet and safe use data on the packaging label, information about its physical properties and health hazards.

SHELF LIFE AND STORAGE

When stored below + 40°C in its original unopened packaging, the grease has a shelf life of 60 months from date of manufacture. Maximum preservation of operational qualities is achieved when stored in a cool room in a tightly closed container.

HEALTH SAFETY INFORMATION

Tixxon products, under normal conditions of use and when observing good personal hygiene, do not pose a health hazard. For more information, visit our website www.tixxon.com or consult your local representative.

APPLICATION



manually,
with a standard
grease gun;



with a central
grease transfer
pump.

!! Every time you should work with extreme care in order to avoid contamination of the grease.

LIMITED WARRANTY TERMS. READ THIS SECTION CAREFULLY

The information provided in this document is offered in good faith and is reliable. However, because the conditions and methods of use of our products are beyond our control, this information should not be used as a substitute for your own tests performed to confirm that Tixxon products are safe, effective, and fully satisfy the end use for which they are intended. Suggestions and recommendations for use should not be taken as an inducement to infringe any patent. We warrant only that this product will conform to its current specifications at the time of delivery.